



LUKI VIETNAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,
HCMC, Vietnam

Tel: 84-8-35534001/2/3/4 Fax: 84-8-35534005/6

Email : info@lukivietnam.com

Website : www.lukivietnam.com

BIDIRECTIONAL FILAMENT TAPE

(LukiTape # 01106-01-125) Specs

Description

Lukitape#01106-01-125 Bidirectional Filament Adhesive Tape based on a polyester film laminated to cross weave fiber glass, which has a good tensile as well as high adhesion.

- It has a good longitudinal and transverse tensile strength as well as high tack and high strength.
- Ideal applications include bunding and strapping heavy goods, securing pallets and reinforce of shipping cartons.
- Remains good adhesion at wide temperature range(depends on the nature and the weight of the sealing materials).

Technical Characteristics

Lukitape#01106-01-125	
Total Thickness, microns	135
Backing	PET film
Reinforcement	Glass Yarn
Adhesive	Hot Melt Pressure Sensitive
Peel adhesion at 180°, N/25mm	40
Holding Power, hr/kg/24mm	>72
Tensile Strength, N/25mm	500
Elongation (at break), %	8
Initial Adhesion	14
Storage life	2 years from the date of making
Best temperature working	15-35°C

Standard Size

Width	Length
24mm, 36mm, 48mm, 50mm, 60mm, 72mm	30m, 40m, 50m, 66m, 100m, 1000m

Core Size (ID): 1.5" and 3 "

Available in other sizes as well.

Storage Conditions: Store in a clean, cool and dry place, avoid sunshine direction. Storage at room temperature. If temperature approach 0°C, product will become harder.

IMPORTANT NOTICE

Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product.

Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application.

LIMITATION OF REMEDIES AND LIABILITIES

If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE LUKI PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.