



# LUKI VIETNAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,  
HCMC, Vietnam

Tel: 84-8-35534001/2/3/4 Fax: 84-8-35534005/6

Email : [info@lukivietnam.com](mailto:info@lukivietnam.com)

Website : [www.lukivietnam.com](http://www.lukivietnam.com)

## PLATE MOUNTING TAPE

(LukiTape # 01603)

### PRODUCT DESCRIPTION

- Product No. : LukiTape # 01603 (Liner: Yellow color)
- LukiTape # 01603 is coated tape for mounting printing plates in the flexographic process. With specially formulated adhesives no residues remain on plate or cylinder when tape is removed.

### APPLICATION

- Mounting photopolymer or rubber plates on small diameter cylinders when high adhesion on plate & cylinder is preferred.

### FEATURES/ BENEFITS

FEATURES	BENEFITS
Rubber Adhesive	<ul style="list-style-type: none"> <li>➤ High initial tack</li> <li>➤ Clean and easy removal</li> <li>➤ No edge lifting, even on small cylinders</li> </ul>
PVC transparent film	<ul style="list-style-type: none"> <li>➤ Provides high flexibility combined with high shear resistance</li> <li>➤ Controlled thickness consistency.</li> <li>➤ Ensures easy removal in one piece.</li> </ul>
Ribbed PVC liner	<ul style="list-style-type: none"> <li>➤ Easy removal</li> </ul>

### TECHNICAL PERFORMANCE

- Carrier : Transparent PVC film
- Adhesive : Natural rubber
- Liner : Ribbed Yellow PVC
- Thickness (w/o liner) : 100 micron
- Tensile strength : 140 N/ 25mm
- Adhesion to steel : Inner side (liner side) 15 N/25mm  
Outer side (open side) 15N/25mm

### NOTICE

- Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

#### IMPORTANT NOTICE

Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product.

Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application.

#### LIMITATION OF REMEDIES AND LIABILITIES

If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE LUKI PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.