

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist., HCMC, Vietnam

Tel: 84-8-35534001/2/3/4 Fax: 84-8-35534005/6

Email: info@lukivietnam.com
Website: www.lukivietnam.com

MASKING TAPE

(LukiTape # 01903 & 01904)-MSDS

1. PRODUCT IDENTIFICATION/SUPPLIER

Description : Masking Tape (LukiTape # 01903, LukiTape # 01904)

- Color: Natural

Creped paper coated with rubber base adhesive

- Supplier : LUKI VIETNAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,

HoChiMinh City, Vietnam

Tel: 84-8-35534001/2/3/4 Fax: 84-8-35534005/6

Hazard Rating: Toxicity=1 Fire=1 Reactivity=0 Special=none

2. COMPOSITION/INFORMATION ON COMPONENTS

No. Weight (%)
1. Natural rubber 9-20
2. Styrene rubber 0-3
3. Hydrocarbon resin 13-24
4. Creped paper 59-60

3. HAZARD IDENTIFICATION/FIRE AND EXPLOSION

Flash Point : not applicable
Auto-Ignition Temperature : not applicable
Lower Explosive Limit : not applicable
Upper Explosive Limit : not applicable

4. EMERGENCY AND FIRST AID PROCEDURES

- Inhalation : No need anticipated

Eye contact: Flush eyes with water for at least 15 minutes. Consult a physician if

irritation persists.

- <u>Skin contact</u> : No need anticipated - Ingestion : No need anticipated

5. FIRE FIGHTING MEASURES

- Unusual Fire and Explosion Hazard: None

Extinguishing Agents:

+ Agents approved for Class A hazard (e.g. halogenated agent, foam, steam) or water fog.

Fire Fighting Procedures:

- + Individuals should perform only those fire-fighting procedures for which they are trained.
- + Personal Protective Equipment:
- + Wear self-contained breathing apparatus and full protective gear.

6. HANDLING AND STORAGE

Handing

Protection gear may not be required in particular in the normal use of this product. It is recommended to wear suitable protective gloves in the ease of direct contact with the adhesive face.

Handle at well-ventilated place so as not to be inhaled the smell of product. It is recommended to install the appropriate equipment of ventilation when the smell of product is spread at working area.

Storage

Store in a cool place.

7. PERSONAL PROTECTION

- Engineering controls

Suitable ventilating equipment should be installed at working area if smells hardly.

Personal protection

Protective gloves : Wear impervious gloves (polyethylene, nitrile rubber) when contact

with the adhesive face.

Protective glasses : Not required in particular.
Protective clothes : Not required in particular.

Exposure guideline

Tackifier : Not established by OSHA and ACGIH.

8. STABILITY AND REACTIVITY

- Stability

Stable under normal handing conditions.

Incompatibility

Strong acids and strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide, carbon dioxide, a bit of alkylphenol and formalin (possibility).

Hazardous polymerization

It will not occur.

9. TOXICOLOGICAL INFORMATION

No information and data as product...

As Tackifier Toxicity data

LD50>2000mg / Kg

10. ECOLOGICAL INFORMATION

Ecological information

Unknown.

Chemical fate information

Unknown.

11. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

12. TRANSPORT INFORMATION

UN NO. Not listed. International classification Not relevant

13. REGULATORY INFORMATION

This product can be identified as "article" by TSCA and CSCL of Japan.

Carcinogenicity information

This product doesn't contain greater than 0.1% of any materials listed as carcinogenic by OSHA, NTP or IARC.

14. OTHER INFORMATION

The information herein is the best of our knowledge and is only related to this specific product No.warranty, either expressed or implied, is made with respect to such information. The recommended handling procedures are believed to be generally applicable. However, it is user's responsibility of review these recommendations in the specific content of the intended use. We reserve the right to revise this MSDS as new information become available. It is recommended to ask for the latest version to our sales division.

The end of MSDS