



# LUKI VIET NAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,  
HCMC, Vietnam

Tel: 84-8-35534001 Fax: 84-8-35534006

Email : [info@lukivietnam.com](mailto:info@lukivietnam.com)

Website : [www.lukivietnam.com](http://www.lukivietnam.com)

## CLOTH DUCT TAPE (LukiTape # 01303)

### PRODUCT DESCRIPTION

- Product No. : LukiTape # 01303
- LukiTape # 01303 is Cloth Duct Tape adopts PE-coated cloth as backing with rubber-resin adhesive coated. It enjoys high tensile strength, excellent moisture resistant, easy tear. It conforms well to irregular surface.

It is a good choice for bundling, heavy carton packing, general maintenance, pipe wrapping, carpet fixing, air-conditioning duct's seam and joint sealing etc.

### TYPICAL PHYSICAL PROPERTIES

- Adhesion : 12 N/25mm
- Thickness : 200 micron
- Elongation : 10%
- Service Temp. : -20~+60°C
- Tensile Strength : 150 N/25mm
- Colour : Silver, Black, White, Red, Yellow, Green, Blue, Beige

### PRODUCT FORM & SIZE AVAILABLE

- **Cut Roll:** 48 / 50mm (2") / 60 / 63mm (2.5") / 72 / 75mm (3") / 96mm / 100mm (4")
- **Log Roll:** 1060mm x 45M / 50M **Jumbo Roll:** 1060mm x 1000M / 1200M / 1350M

### IMPORTANT NOTE

- The data above are typical values only, and should not be used for specifications purpose.
- . Tolerance: Weight and Thickness:  $\pm 10\%$ ; Width:  $\pm 3\text{mm}$ ; Length: Cut Roll:  $\pm 0.3\text{m}$ , Jumbo Roll  $\pm 0.5\%$ .

### STORAGE & SHELF LIFE

12 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

### PRODUCT USE:

It is essential that the user evaluate the product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on products between +10 ~ +40°C (+50 ~ +105 °F).

#### IMPORTANT NOTICE

Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product.

Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application.

#### LIMITATION OF REMEDIES AND LIABILITIES

If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE LUKI PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.