



# LUKI VIETNAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,  
HCMC, Vietnam

Tel: 84-8-3553 4001/2/3/4 Fax: 84-8-3553 4005/6

Email : [info@lukivietnam.com](mailto:info@lukivietnam.com)

Website : [www.lukivietnam.com](http://www.lukivietnam.com)

## TISSUE DOUBLE SIDES TAPE

LukiTape # 01407-MSDS

### 1. PRODUCT IDENTIFICATION/SUPPLIER

- Description : TISSUE DOUBLE SIDES TAPE (LukiTape # 01407)
- Supplier : **LUKI VIETNAM CO., LTD**  
203/9 Dang Thuy Tram Str., Ward 13,  
Binh Thanh Dist, HoChiMinh City, Vietnam  
Tel : 84-8-3553 4001/2/3/4 Fax: 84-8-3553 4005/6

### 2. COMPOSITION/INFORMATION ON COMPONENTS

- Double-Sided PE – CAS NO. 9002-88-4
- TISSUE: – CAS NO. 9004-34-6
- Adhesive: Acrylic – CAS NO. 79-10-7

### 3. HAZARD IDENTIFICATION/FIRE AND EXLOSION

- Physical/chemical hazards, fire and explosion hazards.
- Low risk. The product can burn only in presence of free flames; the fumes therefore developed, can cause eye-watering and asphyxia.
- If the products is handled with care and common sense, than there are no manifest problem related to its use.

### 4. EMERGENCY AND FIRST AID PROCEDURES

- |                          |   |
|--------------------------|---|
| Inhalation :             | Not applicable under normal use conditions.<br>In case of fire, proper protection o respiratory system should be used<br>If necessary ask for medical assistance. |
| Skin contact :           | In case of individual hypersensibility, wash with neutral detergent<br>(soap) and ask for medical assistance.   |
| Ingestion, eye contact : | No precaution is required by standard use.  |

### 5. FIRE FIGHTING MEASURES

- |                            |   |
|----------------------------|---|
| Fire-fighting procedures : | Use water sprays to cool down the surfaces<br>Exposed to fire and to protect personnel. Use self- contained breathing apparatus in closed room, avoid breathing combustion furnes |
| Extingulshing media :      | Water spray, CO2-extinguisher   |

### 6. ACCIDENTAL RELEASE MEASURES

Not appliable.

## 7. HANDLING AND STORAGE

- Storage temperature: Environmental temperature (23+/-2°C)
- Transport temperature: Environmental temperature (23+/-2°C)
- Transport packaging: Cardboard boxes.
- Handling and storage general Information:
  - Keep away from heat and sources of ignition. Goods should be stored in closed packings.
  - Keep in cool, well ventilated place, Keep away from direct sunlight.

## 8. PERSONAL PROTECTION

Not applicable.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance: Solid.
- Colour: -
- Odour: Slightly odorous.
- Solubility In organic solvents: Insoluble, partly soluble, soluble adsorbent depending on solvent type.
- Melting point: Not applicable.
- Boiling point: Not applicable.
- Solubility In water: No.

## 10. STABILITY AND REACTIVITY

Condition to avoid : Direct sunlight.

## 11. OTHER INFORMATION

These informations are based on our knowledge up to today.

They refer exclusively to the above mentioned products and don't stand for guarantee of quality.

End user is supposed to make sure that informations are complete and suitable to any particular use they are appointed.

This sheet cancels and substitutes any previous edition.

The MSDS is supplied by LUKI VIET NAM CO., LTD. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. Final determination of suitability of any material is the sole responsibility of the user. We do not accept liability for any loss or damage that may occur from the use of this MSDS.

☺☺☺☺☺☺