

PLATE MOUNTING TAPE (LukiTape # 01609)-MSDS

1. **Product Identification/Supplier**

- Description : Plate Mounting Tape (LukiTape # 01609)
- Supplier : **LUKI VIETNAM CO., LTD**
203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist, HoChiMinh City
Tel : 84-8-35534001 Fax : 84-8-35534006

2. **Hazards Identification**

Double-side Polyester tape. Odorless.
Not a fire hazard in open areas.
Water fog, foam, CO₂ and dry chemicals can be used on fires.

3. **Composition and Information on Ingredients**

Chemical Name	Weight %	CAS No.
Acrylic Adhesive	40~50	
Release Paper	41~51	[25085-53-4]
Polyester film	9~10	[25038-59-9]
ethyl acetate	<1	[141-78-6]

4. **First -Aid Measures**

Eye contact : Immediately flush with copious amounts of water for at least 15 minutes. Get medical attention.
Skin contact : No potential health effects are anticipated .
Inhalation : No adverse effects anticipated by this route of exposure incidental to proper industrial handling.
If Swallowed : Drink two glasses of water. Call a physician.
Note to physicians : Treat symptomatically. Treatment may vary with condition of victim and specifics of incident.

5. **Fire-fighting Measures**

Flash Point (Method Used): N/A (ASTM D-1929)
Flammable Limits: N/A
Extinguishing Media: water, dry chemical foam, CO₂
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes
Unusual Fire and Explosion Hazards: Any polypropylene and adhesive can be forced to burn by continuous application of intense Heat

6. **Accidental Release Measures**

Sweep up and discard.

7. **Handling and Storage**

Handling : Caution with edge of sheet. After using this sheets, wash hands.
Storage : Keep dry and cool (below 25° C) and away from direct sunlight for quality.

8. **Exposure controls/Personal Protection**

Engineering Controls : Good general ventilation should be sufficient for most conditions. When processing at elevated temperature, provide local exhaust.

Personal protective equipment(PPE) : Respiratory Protection :For most conditions, no respiratory protection should be needed. When processing at elevated temperature, use an approved respiratory protection.

9. Physical / Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O=1)	N/A
Vapor Pressure (mm Hg)	N/A	Softening Point	> 100°C
Vapor Density (Air=1)	N/A	Evaporation Rates (Butyl Acetates=1)	N/A
Solubility in Water	N/A	Decomposition Temperature	N/A

Appearance and Odor

10. Stability and Reactivity

Condition to avoid : Direct sunlight.

11. OTHER INFORMATION

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Luki Viet Nam MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Luki Viet Nam product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Luki Viet Nam product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Luki Viet Nam product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Luki Viet Nam provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Luki Viet Nam makes no representations as to its completeness or accuracy.

In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Luki Viet Nam.

