203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist., HCMC, Vietnam

Tel: 84-8-35534001-2-3-4 Fax: 84-8-35534005-6

Email : info@lukivietnam.com
Website : www.lukivietnam.com

# **DOUBLE SIDED TAPE**

(LukiTape # 01609-04-85)

### PRODUCT DESCRIPTION

- LukiTape # 01609-04-85 is a thin PET carrier tape with acrylic solvent based adhesive, transparent and good adhesion.
- Composition:

Release Paper110g/m <sup>2</sup> Double-Sided PE			
Acrylic Solvent Based Adhesive			
Polyester 0.025mm			
Acrylic Solvent Based Adhesive			

### **APPLICATIONS**

- Permanent bonding of materials such as metal, wood, plastic, paper, glass, ceramics and rubber.
- Ideal for making plastic extrusions self-adhesive especially PVC extrusions for permanent mounting in the furniture industry. Mounting of decorative parts and trims.
- Mounting flexographic printing plate.

# **FEATURES/BENEFITS**

- High quality and strong holding power acrylic adhesive allows for use on a wide variety of surfaces
- Excellent resistance to heat, weathering and thermal creep
- Heavy-duty release paper allows for easy manual handling
- No known hazards
- Application Temperature is –20~80°C

### **TECHNICAL PERFORMANCE**

DESCRIPTION	UNITS	VALUE
Tape thickness	mm	0.10
Material Carrier		Polyester
Color		Clear
Adhesion to Steel,	gf/25mm	1600
Tack, Ball Number		10
Holding Powder	Hr/kg/24mm	24

# STORAGE DETAILS

• Recommended one-year shelf life from date of dispatch if kept at moderate temperatures and humidity levels

01609-04-85 / Update: 30/03/2016

# Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product. Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application. LIMITATION OF REMEDIES AND LIABILITIES If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE Luki PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

01609-04-85 / Update: 30/03/2016