



# LUKI VIET NAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,

HCMC, Vietnam

Tel: 84-8-35534001 Fax: 84-8-35534006

Email : [info@lukivietnam.com](mailto:info@lukivietnam.com)

Website : [www.lukivietnam.com](http://www.lukivietnam.com)

## KRAFT PACKING TAPE

(LukiTape # 02001)

### PRODUCT DISCRIPTION

Luki Tape#02001 adopts poly-coated Kraft as backing, combined with a high performance synthetic rubber-resin adhesive, It is mainly used for carton packaging and sealing.

### TYPICAL PROPERTY TABLE

PROPERTIES	METRIC	TEST METHOD
Total Thickness	120 Microns	PSTC-133 / ASTM D 3652
Adhesion to Steel	12 - 15 N/25mm	PSTC-101 / ASTM D 3330
Tensile Strength	75 N/25mm	PSTC-131 / ASTM D 3759
Elongation	3.0 %	PSTC-131 / ASTM D 3759
Service Temperature	-20 ~ +60 °C	-----
Applying Temperature	+10 ~ 40 °C	-----

### IMPORTANT NOTE

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Weight and Thickness:  $\pm 10\%$ ; Width:  $\pm 3\text{mm}$ ; Length: Cut Roll:  $\pm 0.3\text{m}$ , Jumbo Roll  $\pm 0.5\%$ .

**STORAGE & SHELF LIFE:** 12 months when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.

**SURFACE PREPARATION:** It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

**PRODUCT USE:** It is essential that the user evaluate Luki product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on Luki products between +10 ~ +40°C (+50 ~ +105 °F).