



LUKI VIETNAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,
HCMC, Vietnam

Tel: 84-8-35534001/2/3/4 Fax: 84-8-35534005/6

Email : info@lukivietnam.com

Website : www.lukivietnam.com

PE PROTECTION TAPE

(LukiTape # 03309)

PRODUCT DESCRIPTION

- Product No.: LukiTape#03309
- Colour: Clear

APPLICATION

- Surface Protection

TRANSPORTATION AND STORAGE

- In the case of Packaging is intact, the finished products up to 12-layer stack yards rise. Forbid to transport or storage with organic solvents and other chemicals, avoid sunlight and rain Forbid hard objects direct impact or strongly pushed Stored at a temperature 25+/-10°C, humidity of 60+/-10%.

TECHNICAL PERFORMANCE

- 180°Peeling Strength: 12±4 g/25mm
- Heat Resistance: Stick on ABS Injection Molding Parts, at 70 °C incubator for 24 hours, no glue residue
- Thickness Tolerance: 0.045±6% mm
- Width Tolerance: ± 5 mm
- Backing elongation at break: MD ≥200% ; CD ≥200%
- Backing material: LDPE
- Adhesion :Acrylic Pressure Sensitive Adhesive

NOTE

We suggest the using condition should be: the temperature 15 °C ~ 35 °C , humidity below 80%.
Beyond this condition, the user should have a test.

The application surface is damp or cleanliness, may affect the product viscosity.

If the application surface has oily, organic solvents and other chemicals that could easily leave residue
For the injection molding, because of raw materials that may contain more plasticized, toughening,
and along with the release agent, the user should have a test before using.

The information contained herein is typical values intended for reference and comparison purposes
only. They should not be used as a basis for design specifications or quality control.

IMPORTANT NOTICE

Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product.

Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application.

LIMITATION OF REMEDIES AND LIABILITIES

If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE LUKI PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.