



# LUKI VIET NAM CO., LTD

203/9 Dang Thuy Tram Str., Ward 13, Binh Thanh Dist.,  
HCMC, Vietnam

Tel: 84-8-35534001 Fax: 84-8-35534005/6 Email :

[info@lukivietnam.com](mailto:info@lukivietnam.com)

Website : [www.lukivietnam.com](http://www.lukivietnam.com)

## TEAR TAPE

(LukiTape # 09800)

### PRODUCT DESCRIPTION

- Product No. : LukiTape # 09800
- A polypropylene film with pressure sensitive adhesive applied to one side of the film and release coating on the other side from narrow adhesive-coated plastic.

### APPLICATIONS

- To be applied to the inside surface of modern filmic overwraps, including laminates and papers. Used as an easy opening tear of tobacco, food pharmaceutical and other consumer products.

### PROPERTIES

- Tape Properties

PARAMETERS	UNIT	TEST METHOD	SPECIFICATION
Substrate Type	-	-	MOPP
Adhesive Type	-	-	Acrylic water based
Peel Adhesion	G/25 mm	ASTM D 3330	700 +/- 10%
Film Thickness	micron	ASTM D 3652	125 +/- 10%
Total Thickness	micron	ASTM D 3652	147 +/- 10%
Tensile Strength	Kgs/25 mm	ASTM D 3759	98 +/- 10%
Elongation At Break	%	ASTM D 3759	35 +/-5

### Storage

Store under dry conditions 5<sup>o</sup>C and 25<sup>o</sup>C in the container supplied, ideally at 50% relative humidity. Always keep the container the correct way up, as indicated by the arrow.

### Temperature Usage Range

5<sup>o</sup> C to 50<sup>o</sup> C

### Shelf Life

Stored under the recommended conditions, it is expected to have a shelf life of at least 3 years from the date of manufacture

### IMPORTANT NOTICE

Luki makes no warranties, express or implied, including, but not limited to, any implied warranty or merchantability or fitness of a Luki product for a particular purpose. Luki is not responsible in determining the particular purpose or suitability of application on the user's behalf as the performance of the Luki product may vary under different applications and circumstances thereafter. The materials to be laminated with the product, the surface preparation procedures, choice of product, period of time and environment conditions when applied are factors which can affect the performance of the Luki product.

Given the countless number of possibilities which may affect the performance of the Luki's product, and some of which are within the user's knowledge and control, it is therefore essential for the user to determine whether the Luki's product is fit or suitable for that particular purpose or method of application.

### LIMITATION OF REMEDIES AND LIABILITIES

If the Luki's product is proven to be defective, THE EXCLUSIVE REMEDY, AT LUKI'S OPTION SHALL BE TO REFUND OR REPLACE THE DEFECTIVE LUKI PRODUCT, and within the limits of the purchase price. Luki shall not otherwise be liable for any loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.